

SAFETY DATA SHEET

Issue Date 14-May-2015 Revision Date 20-May-2021 Version 2

PA - B Poly-Astic Sealer Part B

1. IDENTIFICATION

Product identifier

Product Name Poly-Astic Sealer Part B

Other means of identification

Product Code PA - B

Recommended use of the chemical and restrictions on use

Recommended Use Restricted to professional users.

Uses advised against Consumer use

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressSolomon Colors, Inc.Solomon Colors, Inc.4050 Color Plant Road4050 Color Plant RoadSpringfield, ILSpringfield, IL

Springfield, IL Springfie 62702 62702

02102

Company Phone Number 800-624-0261 (US & Canada); 217-522-3112 (Outside North America)

24 Hour Emergency Phone Number 800-373-7542 Use only in the event of an emergency involving a spill, leak, fire, exposure,

or accident involving chemical

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This product is classified as hazardous according to the criteria contained in the Hazard Communication Standard 29 CFR 1910.1200 (known as HCS 2012) and the Hazardous Products Regulations SOR/2015-17 (known as WHMIS 2015).

Respiratory sensitization	Category 1
Skin sensitization	Category 1
Specific target organ toxicity (single	Category 3 (respiratory, central nervous system)
exposure)	

Label elements

Emergency Overview

Danger

Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause an allergic skin reaction

May cause respiratory irritation

May cause drowsiness or dizziness

PA - B 1 / 9 Poly-Astic Sealer Part B



Appearance Viscous Physical state Liquid Odor Low

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
In case of inadequate ventilation wear respiratory protection
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves
Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

Specific treatment see section 4 of the SDS.

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

• Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Parachlorobenzotrifluoride	98-56-6	40 - 55	*
Homopolymer of Hexamethylene Diisocyanate	28182-81-2	< 50	*
Hexamethylene-1,6-Diisocyanate	822-06-0	< 0.5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice In case of accident or unwellness, seek medical advice immediately (show directions for

use or safety data sheet if possible).

Eye contact Do not rub affected area. Immediately flush with plenty of water. After initial flushing,

remove any contact lenses and continue flushing for at least 15 minutes. Call a physician.

PA - B 2 / 9 Poly-Astic Sealer Part B

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. In the case of skin irritation or allergic reactions see a physician.

Inhalation Move to fresh air in case of accidental inhalation of vapors or decomposition products. May

cause allergic respiratory reaction. If breathing is irregular or stopped, administer artificial

respiration. If symptoms persist, call a physician.

Ingestion If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

Most important symptoms and effects, both acute and delayed

Symptoms May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause

allergic skin reaction. Isocyanate vapors or mists at concentrations above the exposure guidelines can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) with symptoms of runny nose, sore throat, coughing, chest congestion, shortness of breath, and reduced lung function (breathing difficulty). Persons with preexisting, nonspecific bronchial hyperactivity can respond to concentrations below the exposure limits of guidelines with symptoms similar to an asthma attack (or asthma-like symptoms). Exposure well above the exposure guidelines may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). Chemical or hypersensitivity pneumonitis, with flu-like symptoms (e.g. fever, chills), has also been reported with isocyanate exposure. These symptoms can be delayed up to several hours after exposure. These effects are usually reversible. May cause dizziness, drowsiness, or irritation. Symptoms affecting the

respiratory tract can also occur several hours after overexposure.

Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon Dioxide, Foam, Sand.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

In the event of fire, cool tanks with water spray. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Exposure to heated diisocyanate can be extremely dangerous.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Hydrogen cyanide. Isocyanate. Isocyanic Acid.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined

areas. Avoid contact with skin, eyes or clothing. Use personal protective equipment as

required. Remove all sources of ignition.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Contain and collect spillage with

non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

Methods for cleaning up

Use clean non-sparking tools to collect material and place it into loosely covered plastic

containers for later disposal. Dike for later disposal and cover with wet sand or earth. For

disposal information see section 13.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Do not breathe vapors or mists. Used adequate ventilation to keep airborne levels below

exposure limit guidelines. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.

Do not store near combustible materials.

Incompatible materials Strong oxidizing agents. Water. Strong bases. Alcohols. Copper.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Parachlorobenzotrifluoride 98-56-6	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m³ F (vacated) TWA: 2.5 mg/m³	IDLH: 250 mg/m ³ F
Hexamethylene-1,6-Diisocyanate 822-06-0	TWA: 0.005 ppm	-	Ceiling: 0.020 ppm 10 min Ceiling: 0.140 mg/m³ 10 min TWA: 0.005 ppm TWA: 0.035 mg/m³

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Do not eat, drink or smoke when using this product. Handle in accordance with good

industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Viscous **Appearance** Odor Low

Color No information available Odor threshold No information available

Property Values Remarks • Method

No information available pН No information available Melting point/freezing point Boiling point / boiling range 130.3 °C / 266.5 °F Flash point >93.3 °C / >200 °F **Evaporation rate** No information available Flammability (solid, gas) No information available

Flammability Limit in Air

No information available Upper flammability limit: Lower flammability limit: No information available Vapor pressure No information available Vapor density No information available

Specific Gravity 1.23 Water solubility

No information available Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available No information available Kinematic viscosity Dynamic viscosity No information available No information available **Explosive properties** Oxidizing properties No information available

Other Information

Softening point No information available Molecular weight No information available No information available **VOC Content (%)**

10.34 lb/gal **Density**

No information available **Bulk density**

10. STABILITY AND REACTIVITY

Reactivity

Contact with moisture, other materials that react with isocyanates, or temperatures above 350 F may cause polymerization.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

Strong oxidizing agents. Water. Strong bases. Alcohols. Copper.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Hydrogen cyanide. Isocyanate, Isocyanic acid.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product InformationThe product has not been tested The product is classified based on the mixture

components.

Inhalation Avoid breathing vapors or mists. May cause sensitization by inhalation. May cause

drowsiness or dizziness. Irritating to respiratory system.

Eye contact Avoid contact with eyes. Contact with eyes may cause irritation.

Skin Contact May cause sensitization by skin contact.

Ingestion Do not taste or swallow. Harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Parachlorobenzotrifluoride 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg(Rabbit)	= 33 mg/L (Rat) 4 h
Homopolymer of Hexamethylene Diisocyanate 28182-81-2	-	-	= 18500 mg/m ³ (Rat) 1 h
Hexamethylene-1,6-Diisocyanate 822-06-0	= 738 mg/kg (Rat)	= 593 mg/kg (Rabbit)	= 0.06 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause

allergic skin reaction. Isocyanate vapors or mists at concentrations above the exposure guidelines can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) with symptoms of runny nose, sore throat, coughing, chest congestion, shortness of breath, and reduced lung function (breathing difficulty). Persons with preexisting, nonspecific bronchial hyperactivity can respond to concentrations below the exposure limits of guidelines with symptoms similar to an asthma attack (or asthma-like symptoms). Exposure well above the exposure guidelines may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). Chemical or hypersensitivity pneumonitis, with flu-like symptoms (e.g. fever, chills), has also been reported with isocyanate exposure. These symptoms can be delayed up to several hours after exposure. These effects are usually reversible. May cause dizziness, drowsiness, or irritation. Symptoms affecting the

respiratory tract can also occur several hours after overexposure.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Not classified. (Based on mixture components.).
Serious eye damage/eye irritation Not classified. (Based on mixture components).

Serious eye damage/eye irritation Not classified. (based on mixture components).

Sensitization Skin Sensitizer Cat 1. May cause an allergic skin reaction. Respiratory Sensitizer Cat. 1.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity
Carcinogenicity
Not classified. (Based on mixture components).
Not classified. (Based on mixture components).
Not classified. (Based on mixture components).

STOT - single exposure STOT SE 3 - Respiratory System. May cause dizziness or drowsiness. May cause irritation

of respiratory tract.

STOT - repeated exposure Not classified. (Based on mixture components.). Aspiration hazard Not classified. (Based on mixture components).

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 > 5000 mg/kg

 ATEmix (dermal)
 3686.7 mg/kg

 ATEmix (inhalation-gas)
 >20,000 ppm

 ATEmix (inhalation-dust/mist)
 10.103 mg/l

 ATEmix (inhalation-vapor)
 108.700 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Parachlorobenzotrifluoride	3.7
98-56-6	

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

14. TRANSPORT INFORMATION

DOT Not Regulated (Single Container < RQ)

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies **EINECS/ELINCS** Complies Complies **ENCS IECSC** Complies **KECL** Complies Complies **PICCS** Complies **AICS**

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

See section 2 for more information

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Hexamethylene-1,6-Diisocyanate	100 lb	-	RQ 100 lb final RQ
822-06-0			RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
Parachlorobenzotrifluoride - 98-56-6	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Parachlorobenzotrifluoride 98-56-6	Х	-	-
Aliphatic Isocyanate	Х	Х	-

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 1 Reactivity 1 Physical and Chemical Properties -

HMIS Health hazards 1 Flammability 1 Physical hazards 0 Personal protection X

Prepared By Solomon Colors - Lab Technical Services

Issue Date 14-May-2015 Revision Date 20-May-2021

Revision Note Periodic Review

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet